अधिष्ठाता यांचे कार्यालय, शासकीय आयुर्वेद रुग्णालय, वजिराबाद, नांदेड. OFFICE OF THE DEAN,

GOVT. AYURVED HOSPITAL, VAZIRABAD, NANDED.

Email ID :- gahnanded@gmail.com दुरध्वनी क्रमांक :- (०२४६२) २३२८६७ फॅक्स क्र.२३४०२६

जो क शाकारता/क्षेप्रधीभोडार/

12000

प्रति,

विषय :- <u>शासकीय आयुर्वेद रुग्णालय, नांदेड.</u> यंत्रसामुग्री/उपकरणे इत्यादी पुरवठा करण्याकरिता दरपत्रक सादर करणे बाबत.

उपरोक्त विषयाच्या अनुषंगाने आपणांस कळविण्यात येते की, जिल्हा वार्षिक योजना (सर्वसाधारण) २०२०-२०२१ अंतर्गत मंजुर निधी शासकीय आयुर्वेद महाविद्यालय व रुग्णालय, नांदेड यांचे बळकटीकरण तथा श्रेणीवर्धन याकरिता मंजुर निधीतून यंत्रसामुग्री/उपकरणे खरेदी करण्याकरिता दरपत्रके मागविण्यात येत आहेत. सदर यंत्रसामुग्रीचे नावं, नग व विर्निदिष्टे (Specification) सोबत जोडण्यात आले आहेत.

उपणांस सुचित करण्यांत येते की, रुग्णालय व महाविद्यालय करिता आवश्यक यंत्रसामृग्री/उपकरणे इत्यादी पुरवठा करण्यांकरिता सोबत जोडण्यात आलेल्या विनिदिष्टेनुसार (Specification) खालील नमुद यंत्रसामुग्रीचा पुरवठा करण्याकरिता कमीत कमी दराची मोहोरबंद पाकीटातील दरपत्रके दिनांक ०८.०२.२०२१ रोजी सायं ०५:०० वाजेपर्यंत पोहोचतील अशा बेताने अधिष्ठाता यांचे कार्यालयात खालील नमुद अटी व शर्तीच्या अधिन राहुन सादर करण्यांत यावीत.

अ.क्र.	<u> </u>	कालावधी
?	दरपत्रक सादर करण्याचा कालावधी	दि. २९/०१/२०२१ ते ०८/०२/२,०२१ (या कार्यालयीन कामाकाजाच्या दिवशी व वेळेत शासकीय व स्थानिक सुट्टीचे दिवस वगळुन सकाळी १०-०० ते सायं ०५-०० वाजे पर्यंत
२	दरपत्रक उघडण्याचा दिनांक व वेळ	दि. ०९/०२/२०२१ रोजी सकाळी ११-०० वाजता
3	दरपत्रक उघडण्याचे ठिकाण	अधिष्ठाता शासकीय आयुर्वेद रुग्णालय, नांदेड यांचे दालन.

अटी व शर्ती

- १. दिनांक ०८/०२/२०२१ रोजी सायंकाळी ०५:०० वाजल्यानंतर प्राप्त होणाऱ्या दरपत्रकाचा विचार केला जाणार नाही.
- २. दरपत्रक सादर करतांना अशा प्रकारच्या खरेदीवर शासनाकडुन आकारल्या जाणारे विविध कर (टॅक्सेस) स्वतंत्रपणे नमुद करावे.
- ३. दरपत्रक सादर करतांना जी.एस.टी. क्रमांक नमुद असलेल्या लेटरहेड वर सादर करावे.
- ४. ज्या यंत्र सामुग्री करिता दरपत्रक सादर करण्यात येत आहे. ते आय.एस.आय. चिन्हांकित असेल तर ठळकपणे नमुद करावे.
- ५. दरपत्रक सादर करणाऱ्या दरपत्रकाचा किंवा संस्थेच्या दरपत्रक प्रक्रियेत भाग घेणाऱ्या अन्य संस्थेमध्ये थेट स्वारस्य असु नये तसे आढळल्यास दोन्ही किंवा अधिक दरपत्रके नाकारण्यात येतील. याकरिता सोबत जोडण्या आलेली हमी पत्र दरपत्रक धारकास सादर करणे बंधनकारक राहील. (सोबत हमीपत्र विहित नमुण्यात सादर करावेत)

- ६. यंत्रसामुग्री खरेदी पश्चात यंत्रसामुग्री करिता देण्यात येणारा हमी कालावधी (वारंटी) कालावधी ठळकपणे नमुद करावा
- ७. दरपत्रका सोबत ज्या यंत्रसामुग्री करीता दरपत्रक सादर करण्यात येत आहे. त्या यंत्रसामुग्रीची विस्तृत माहिती असलेली माहिती पत्रक (Products catslogue) जोडावे.

८ दरपत्रक सादर करतेवेळी मोहोरबंद/सिलबंद पॉकीटावर यंत्रसामुग्री करिताचे दरपत्रक असे स्पष्ट करावे.

- श. खरेदी प्रक्रिया यणस्वी दरपत्रक स्विकारण्यापुर्वी किंवा यश्स्वी दरपत्रक स्विकारण्यात आल्यानंतर देखील कोणत्याही वेळी लेखी नमुद करावयाचा कारणामुळे रद्द करण्याचे अधिकार हे कार्यालय राखुन ठेवीत आहेत.
- १०. विहित कालावधीत प्राप्त दरपत्रके दिनांक ०९/०२/२०२१ रोजी सकाळी ११-०० वाजता अधिष्ठाता यांच्या दालनाल उघडण्यात येतील त्यावेळी कंपनीच्या एका प्रतिनिधीस स्वखर्चान उपस्थित राहण्यास मुभा राहील.
- ११ दरपत्रक उघडल्यानंतर आपण सादर केलेल्या यंत्राच्या विर्निदिष्टे (Specification) नुसार सदर यंत्राची प्रत्यक्ष पडताळणी व आवश्यकता वाटल्यास चाचणी रुग्णालयातील संबंधित तज्ञामार्फत करण्यात येईल त्याकरिता आपण आवश्यक ती व्यवस्था करुन ठेवावी.
- १२. पुरवठादारांने सदर खरेदी संदर्भातील आवश्यक ती माहिती या सोबतच्या Annexure-B मध्ये सादर करावी.

१३. प्रत्येक यंत्रसामुग्री/उपकरणे करिता स्वतंत्र दर पत्रके सादर करावीत.

१४ खरेदी प्रक्रियेचा अटी व शर्तीमध्ये कोणताही बदल करण्याचा अधिकार अधिष्ठाता शासकीय आयुर्वेद रुग्णालय, नांदेड हे राखुन ठेवीत आहेत.

> (डॉ.वाय.आर.पाटील) अधिष्ठाता

शासकीय आयुर्वेद रुग्णालय, नांदेड

सहपत्र (Annrxure)- A शासकीय आयुर्वेद महाविद्यालय,नांदेड. SPECIFICATION OF....

~	ন ম
	दरपत्रकाब्दारं आवश्यक असलेले विनिर्दिष्टे Quotation Specification as asked in the quotation
	पुरवठादाराने प्रस्तावित केलेली तत्सम विनिर्दिष्टे कंपनीच्या नावासहित Equivalent Specifications quoted by the supplier with the name of the manufacturer
	पुरवठादाराने नमूद केलेली विनिर्दिष्टे दरपत्रकान्वये विचारणा करण्यांत आलेल्या विनिर्दिष्टानुसारच आहेत किंवा नाही. प्रत्येक बाबीसमोर होय किंवा नाही स्पष्टपणे नमूद करावे. Whether the Specification quoted by the supplier is as per specification asked for indicated against each item clearly YES/NO
	पुरव दरपत्रव क विनिर्दि असल्या by करावे ॥ or per spe or should b

पुरवठादाराने नमूद केलेली विनिर्दिष्ट दरपत्रकान्वये विचारणा करण्यांत आलेल्या विनिर्दिष्टे यामध्ये काही बदल वा तफावत असल्यास प्रत्येक बाबीसमोर स्पष्टपणे नमूद करावे. If the Specification quoted is not a per specification then variation/deviation should be clearly indicated against each iter asked for.

Annexure-B

कंपनीच्या लेटरहेडवर खालील नमूद तपशिलाप्रमाणे माहिती भरणे.

प्रति, अधिष्ठाता शासकीय आयुर्वेद रुग्णालय, वजिराबाद, नांदेड.

जिल्हा वार्षिक योजना (सर्वसाधारण) - २०२०-२०२१

····या यंत्रसामुग्री करिताचे दरपत्रक

अ.	तपशिल	आवश्यक माहिती वा प्रमाणपत्रे जोडण्यात आलेली आहेत
豖.		किंवा कसे
?	पुरवठादाराचे नावं	
7	क्पंनीचा पत्ता, दुरध्वनी ई-मेल आयडीसहीत	
3	कंपनीचा नोंदणी क्रमांक (Registration No.)	
8	यंत्राचे नावं आणि मॉडेल क्रमांक	
ų	विर्निदिष्टे (सोबत जोडण्यात आलेल्या	
	सहपत्रानुसार) Annexure-A	
3	G.S.T. No.	
و	शासनाचे कर	· ·
6	इतर कर	
९	I.S.I Mark इ(आयएसआय चिन्हाकिंत आहे किंवा कसे ? असल्यास तत्संबंधीचे प्रधिकरणाकडील प्रमाणपत्राची छायांकित प्रत जोडण्यात आली आहे. किंवा कसे ?)	
१०	उत्पादक असल्यास तसे नमुद करावे अथवा प्रधिकृत पुरवठादार असल्याबाबतचे उत्पादक कंपनीचे पत्र.	
99	सदर यंत्राचा इतर शासकीय/निमशासकीय कार्यालयास पुरवठा केला असल्यास अशा कार्यालयाचे पत्ने व दुरध्वनी क्र.अथवा पुरवठा आदेशांची छायांकित प्रत.	
१२	हमी कालावधी (Warranty Period).	
१३	यंत्राची माहिती पुस्तिका/पत्रक	
१४	हमीपत्र	
१५	इतर अटी व शर्ती असल्यास	

स्थळ :-

ठिकाण :-

हमीपत्र -१ (Undertaking)

मी M/s
पत्ता :
लेखी हमी देत आहे की, आपल्या कार्यालयामार्फत
खरेदी करणेसाठी राबविण्यात येत असलेल्या दरपत्रक प्रक्रियेत मी भाग घेत असून माझे
किंवा माझ्या संस्थेचे खरेदी प्राधिकारी / खरेदी समिती वा कार्यालयाशी कोणत्याही प्रकारचे
हितसबंध / संघर्ष नाहीत तसे आढळून आल्यास माझे दरपत्रक नाकारण्यात यावे वा अपात्र
समजण्यात यावे.
स्थळ :-
पुरवठादारांच्या अधिकृत स्वाक्षरी व शिक्कासह
हमीपत्र -२ (Undertaking)
मी M/s
पत्ता : लेखी हमी देत आहे
की, आपल्या कार्यालयामार्फत खरेदी करणेसाठी
राबविण्यात येत असलेल्या दरपत्रक प्रक्रियेत मी/माझी संस्था केवळ एकच दरपत्रक सादर करीत आहे.
त्याचप्रमाणे दरपत्र प्रक्रियेत भाग घेणाऱ्या अन्य संस्थासोबत माझा/माझ्या संस्थेचा कोणत्याही प्रकारचा प्रत्यक्ष
अप्रत्यक्ष सबंध वा सहभाग नाही तसे आढळून आल्यास माझे दरपत्रक नाकारण्यात यावे वा अपात्र समजण्यात
यावे.
ਅਲ :-

पुरवठादारांच्या अधिकृत स्वाक्षरी व शिक्कासह

दिनांक :-

GOVT. AYURVED HOSPITAL, VAZIRABAD, NANDED. PURCHASING OF INSTRUMENTS & MACHINERY UNDER (D.P.D.C) BUDGET 2020-21

		INCONCENTO & MACHINEZ CONDEX (D.T.D.C) DODGE	17-070-71	
Sr.No	Name Instruments & Machinery	Specification	Qty,	Rate Per Unit
	Cautery Machine	Microprocessor based IGBT Technology		
		Tissue Response Technology CE, ISO 2001:2008, ISO 13485:2003, IEC 60601-1		2
		Cardiac protection circuit		
		Endo cut facility		
		Separate Monopolar / Bipolar system (Two		
		different footswitch		
		for simultaneous use of machine by two user)		
		Louvers & fans for heat dissipation		
		Any accessories compatible		
		(Reusable accessories more prefer)		
		Upgradation facility		
		Less Inermal spread		
		Component level machine manufacturing		
		to avoid problem occurs in SMD		
		Onsite repairable component level servicing		
		Stand by machine network at local area		
		Lowest servicing price		
		Local service center at local area since 5 years		
		Particulers max power (watt)		
		pure cute 400 w		
		Bleand 1 250 w		
		Blend 2 200 w		
		spray-120 w		
		rorce-150 w		

Infant/neonatal Warmer with 1. German made imported ceramic heater with pressucitiation unit parabolic reflector microprocessor base control temperaturecontroller, air and manual control with LCD Screen, high temp sensor for high temp cut off at 39 degree. Swivelling source box for x-ray. Oxygenation - inbuilt flow suction apparatus with pressure control. Incubation providing complete	Examination Table Size -72"x24"x30 "ht Top design in two section one top with coach & another head pannel for head low & head eached assembly tops are made in M.S. surgery gauze providers three drawerswith lock & three lockers provide system with heavy handle attached one single step privide total coach expiry powder coated in colour combination	Stainless steel Dressing Trolley frame - 25 mm x25mm ss square tube frame with shelves with railling ontop shelf Trolly mounted oss bowl 360mm diminter ss bucket 300 diameter	Vertical Autoclave Single drum Internal capacity -22 Litre 2.00kw chamber dimension -10"x 59.g(15 psi-17 psi) sterlizing 121'c average-<=±1'c sterlization Time- 99 min construction -double/triple chamber (304 stainless steel) inne wool wastle countainer - stainless safety & interlock device door lock redial locking, safety valve, low wa power supply -220 volts/440 volts.	soft-100w Biopolar force coag -80 w Biopolar cut-80 w Operating frequency 300 Khzmint Weight-6.8 kg Rimoundion-300><140><450+
1. German made imported ceramic heater with p parabolic reflector microprocessor base control temperaturecontroller, air and manual control with LCD Screen, high temp sensor for high temp cut off at 39 degree. Swivelling source box for x-ray. Oxygenation - inbuilt flow suction apparatus with pressure control. Incubation providing complete	Size -72"x24"x30 "ht Top do with coach & another head peached assembly tops are reproviders three drawerswith system with heavy handle attotal coach expiry powder coach	length-1080 mm width 490r frame - 25 mm x25mm ss s shelves with railling ontop s ss bowl 360mm diminter ss	Internal capacity -22 2.00kw chamber dimens 59.g(15 psi-17 psi) sterlizati average-<=±1°c sterlizati 99 min construction -dou chamber (304 stainless s wool wastle countainer - safety & interlock device redial locking, safety valv power supply -220 volts/	soft-100w Biopolar force coag -80 Biopolar cut-80 w Operating frequency 30 Weight-6.8 kg Rimoundion-300><140>
	Size -72"x24"x30 "ht Top design in two section one top pannel fixed with coach & another head pannel for head low & head up position on eached assembly tops are made in M.S. surgery gauze sheet coach providers three drawerswith lock & three lockers provide locking system with heavy handle attached one single step privinding at below total coach expiry powder coated in colour combination.	length-1080 mm width 490mm heigth-840 mm frame - 25 mm x25mm ss square tube frame with two stainless steel shelves with railling ontop shelf Trolly mounted on 100mm dia castors ss bowl 360mm diminter ss bucket 300 diameter	Internal capacity -22 Litre 2.00kw chamber dimension -10"x18" working pressure 1.2 kg flcm 59.g(15 psi-17 psi) sterlizing 121'c to 134.c (150.c-optional) heat average-<=±1'c sterlization Time-25 to 30 Minutes digital timmer - 0 to 99 min construction -double/triple wall & ss4mp construction outer chamber (304 stainless steel) inner chamber -304ss insulation-glass wool wastle countainer - stainless steel Door -Lid - foot+lifted with safety & interlock device door locking type -radial type safety features redial locking, safety valve, low water detector & pressure interlock power supply -220 volts/440 volts.	w 0 Khzmint ~450+
_	-	_		

ω		7	6
Spirometer with printer		B.M.I. Machine	Electrical Cervical & Lumbar Traction Machine (LCD)
Examine lung function related parameters for patients. Accuracy 85-100% Alarm system: Low & Samp; High Model: SP-100, Printed report, PC based spirometer along with latest window version with adequate aunthetic software	Machine should have - Voice input 1. Self weight - approx 30 Kg 2.Self height - 250 cm (approx) 3. Operating temp -0° to 50° 4. Power supply - 250 V.A.C. Should be supplied with adequate cables wires 5. weighing capacity - 200 Kg 6. weighing accuracy - upto 100 gm 7.Height range -(min) 50 to 200 cm 8.Height accuracy -(min)0. 5cm 9. Plat form size- (max) 360 x 300 mm 10.Guarranty -(min) 1 year 11.Annual Maintenance- upto next four years	B.M. I. Machine 24 col.dot Matrix	Acrylic panels with head up and down facility Lower three drawer facility Main supply 220v r0 HZ .Consumption - 85 watts .Lumbar Force 15-45 kg with doublers upto 90 kg .Cervical force - 3,4.5.6,7,8,9,10,11,12,13 kg.Model selection -Separate switch .Timer - Digital (0-99 min) with AUTO Alarm.Hold time - 20,40,60,80 sec.Rest TIME 1,5,10,15,SEC .Weight 10 kg .Dimension (H#W #L) - 30#31#28 CM
_		_	_

	T				
14	13	12	1	10	9
Warmer with LED double surface phototherphy	Syring pump	NIBP multipara Monitor	OT care or Fumigation machine	Glucometer	Massage table with attachements
Photography latest high bright super flex LED double surface. Phototheraphy with digital timmer surface photography with digital timmer german meck ceramic heater with parabolic reflector unit made with high quality FRR fiber for safety clear acrylic base for bottom surface phototherapy with Xray casste compatment, lowerty for utility, mounted anti skid caters with locking facilities, ovl space baby tray with three side collapsiable acrylic walls both side moniter (bracked, I V stans to mount multiple syringe pumps.	Automatic detection of syringe size capacity ,Flow rate can be change during infusion,3 level ,Occlusion alarm limit setting, Bolus facility for fast delivery of drug , Automatic rate calculation with volume and time limit, Syringe 5, 10, 20, 30, 50, 60cc, 9.6 volt, 1300mAm, Battery backup 5-6hrs/ 2.3kg, 306×135×127mm dimensions .	5 Parameter — SPO2, ECG, NIBP, RSPIRATION, TEMP, LCD display, ECG lead mode — 5 lead mouse, keyboard operation applicable, ultra quite fan less design, multiple working modes option, NIBP assisted vein puncture. Display — 12.1 inch, HR range 15-380 bpm, suitable for neonates and paediatrics, alarm indicator for ECG, SPO2, NIBP, RSPIRATION. RESP 2-temp and Arrhythmia indicator, charge lite battery 500, NIBP measurement data can be stored and recall, reausable, NIBP Cuff pediatric size 3 sets	Fumigation machine with 304 stainless steel body, Aerosol disinfector fumigator, pre fitted liuid flow control valve, portable, 5 lit tank capacity, 230 V, 50 Hz,		Stainless steel 304 grade, pine wood and polycarbonated Height:-30" Weight:-85 kg. Measurment:- Length 7 feet width 3 feet height 2.5 feet. Weight bearing capacity 150 Kg Attachement:- 1 Attached vaman peeth.2. Attached shirodhara stand 3. Attached sarvang dhara stand 4. Attached basti stand. 5. foot rest 6. traction. 7. Uttarbast.
- ->	_		_	_	_

Inst	(H)						19	The state of the s	17	16	-7
Instrument cabinet	Electric Weiging machine	Curtain Stand	Bed pan	Autoclave drum	Otoscope (paediatric)	Rediatric Resuscitation kit	Panchakarma table with shirodhara yantra	Digital BP apparatus	Manual BP apparatus	Stadiometer	Nadi swedanayantra
Non Rusting, Non magnatic, size = 960x400x1750mm epoxy coated mild steel frame work stainless steel hottam	Electronic digital weighing Platform scale with stand,weighing capacity upto 200 Kg	3 face exam room privacy screen, Stainless steel body, with wheels at bottom, folding facility of height 60 inch*24inch size	Stainless steel, Non Rusting, Non magnatic	Stainless steel, Size 11"x9" – 1 unit, 8" x 9" – 1 unit.	Fiberoptic otoscope compact pocket, colour blue, replaceable and rechargeable batteries with mini Nt table charger, 4 reusable tips and 10 disposable tips, size 12x7x4 cm	Steel body laryngoscope with straight and curved blades no 2,3 and 4, AMBU bag 750ml capacity with appropriate masks, ET tubes no.4,4.5,5 and 6 one each.	Standard wooden specialised table with steel stand with pot attachment, Metallic shirodhara pot with capacity 1-2 litre with chain attachment. Wooden table with curved edges of size 6 ft x 2.5 ft with standard height, four corner side holes for drainage of medicated oil.	Fully automatic, operating oscillometric principle, pediatric cuff with intelliSence technology, body movement detection, hypertension indicator, irregular heart beat detection.	Mercury	Measure height from 0 to 180cm.	Five litre stainless steel heavy bottom cooker with 4 meter rubber tube.
_	_	_	_	_	٦	_	ـــ	٠.	. احد	ــــــــــــــــــــــــــــــــــــــ	-

	I	Т	Т	T	T					
37	36	35	34	٤	32	ಷ	30	29	28	27
Inverter 180 (12 V) with battery UPS	Mixer Heavy Duty	Kadha Galani (Steel) 6 No.	Kadhai (Iron) 22cm x 22cm	Cardiac Monitor	Electric Steam Inhailer	Foetal Doppler	Sterilizer	Obstretic Table	Enema cane	Anesthesia Trolly
180 VA (12V) Invertor with Battery	550 watt,230 volt ,3 speed control,multipurpose,stainless steel lead,with 3 pot set	Stainless steel Galani of standed quality	Iron material, of standerd of size (22cm x 22cm)	inbuilt handle ,monitor with adult paediatric use disply of SpO2,ECG,NIBP,Pulse.	Plastic body, of any standerd quality	Portable faetal doppler with clearly sound 2 Mhz, probe with LED disply, Faetal Heart rate, battery backup system/ artificial battery input system in case of electricity failure	30 cm x15cmx12.5cm -Electric supply of200 watt -with hinged lid ,fitted with immersion rod & water outlet tap -Stainless steel body -Thermostatic & electric shock preventing system -Tray lifting system	72*22*30 LWH diamentions.3 section cushioned top with stainless steel bowl, Height adjustable, pair of knee crutches, bach rest, seat adjustable by hand lever	Plastic body with capacity of 1 liter, with 1m plastic tube and nozzles of various shapes	Stainless steel -casters wheel with lock -650x420x1020 mm -8 drover -1 sliding shelf -1waste basin -1doughe can -oxygen holder stand
	1	1	1			1		_	_	-

47	46	45	44	43	42	41	40	39	38
Haematocrit Tube	Binacular Microscopes with Oil Immersion	B.P. Handle	Draffin's bipod stand with plates	U.V light instrument sterilization cabinet	Foreign body spud	Chalazion scoop/ currete	Chalazion clamp	Schiotz tonometer	Bipolar Ophthalmic Cautery
Blood Sedimentation Tubes of Borocillate glass Suitable for determining sedimentation rates & Volume of Packed cells ,the values stated in SI units.ragarded as standards.	Body Interchageable, inclined binocular body, 360deg rotable head, Eyepieces-Highest quality 10X wide angle antifungal eyepiece, objectives parfocal, antifungal coated 4X, 10X, 40X & 100X(oil Immerssion) with plan achromatic correction. Optical system-infinity corrected, Stage Horizantal mechanical stage, preferably 100 x 140 mm with fine vernier graduations designed with convenient coaxial adjustments for slide manipulation preferably through 30 x 70 mm. Sub stage-Abbe condensor focusable continuosly variable iris diaphragm.	stainless steel No-7 - 2 No.4-2		A high output , 10,000 hr rated, 8 watt, 254mm, ultraviolet bulb of size (G8T5,2pin, 12" long), grounded power cord (220V, 7' long)	Stainless steel, pointed tip	Stainless steel, small-2 Medium-2	Stainless steel medium-2 Large 2	All vital parts are made up of aluminium other parts are BRASS crome plated complete in case. Perfect reading of scale with rd pointer supplied with 3 weight (5.5gm, 7.5gm, 10gm), with conversion table. Precision measurement on a scale of 0-20subdivisions, and 0 to -1 subdivisions, high quality agate bearing	Radiofrequency- 455-515KHz, output RF power- 5-7W, input supply-220V/50Hz, reusable forceps, erasers, cables, foot switch control, audible indications, 0-9 level variable power output, test certificate and instruction leaflet
			\ -	_	1	_	_	_	_
									e,

101	100	99	98	97	96	95	94	93	92	91	90	89	88	87	. 86	85	84	83	82	81	80	79	78	. 77
American Thali	LED Board Smart Board	Butter Milk Ravi	Electronic Weight Machine with Display	Milk Measurment Cup	Tea Thermos	Oil Kettle	Steel Egg Tray	Surving Bowl	Big size plate (Aluminium)	Steel Bucket	Steel Bins	Plastic Bins	Steel fork tweezers	Cheat Rolling pin	Beehive (dike)	Steel reversals	steel basket	long frying pan	granaries	Tea strainer	Sieve the flour with plates	steel Bowl	Knife	Steel Plate
Stainless steel, molded 5 compartment thali.	Interactive LED Smart board (LED flat panel) size-86" Display area - 1895x1066 mm Resolution :- 3840x2160 Display colours - 10 bit Lite time :- >30000 hours next generation anti glare glass Infrared touch.	Stainless steel	ISI mark 100 kg,	100 gm,200gm,1 ltr	Stainless steel 3 ltr	Stainless steel ,size 3 kg	Stainless steel	Stainless steel		5 litr, 10 ltr with cover plate	Stainless steel	Standard quality 1kg size	Standard quality	Wooden rolling pin	Stainless steel, Wooden	Standard quality	Stainless steel with cover plate		Stainless steel 100 kg ,50 kg ,20 kg	Standard quality	Standard quality	Stainless steel	Standard quality	Stainless steel
4	- حـ		. اح	٠.	_	_	_	_	_	_	_	ے .	2	۔ احد	ا د	_	_ ا	اد	۱	۷	۔ ا		_	_
																					- Bi			2

108 Rotary microtome	107 Foot Streps	106 Biomtric Machin (Iris/Face)	105 Modular Kitchen Storge & Modular washbBasin in S.S.	104 Chapati Bhatti with two Burner Stove in S.S. & Exhaust Chemni	103 Digital Camaera for Mocroscope	102 Microscope
Section thickness setting -05-60 щ mn from 0.5 щ mm -2 щ mm increment from 20ml -20 щ mn in 1 щ inrements from 20 щ m-60 щ in 5 щ mn in i5 щ mn incremnts Vertical strake - 60 mm specification orientation - horizantal 8°, vertical 8° Object feed - 28 mm Max sectiony area - 602 mm x 50 mm microtone should be supplied complete as above with disposable blade holder for both low & high profile blades, a sample pack of 10 each disposable blades & universal specimen clamp & universal	Two Stapes size, Steel, Painted, 6" 2x2" wide			Burner Heavy Gause Steenless Steel (Modular) Chemni	roscope Digital camera for magnus trinocular Led microscope model- NX21i-TR with 0.5XTR adopter.	clinical trinocular microscope with battery backup body Aluminium diecast body. Focusing system- co-axial coarse & Focus range-20 mm focous range - 0.25mm condenssor with perture ivis diagram illumination- 3 w LED 4x, 0.10 / 18.5m 10X 0.25/10.6mm loaded) 0.65/0.6mm loaded) 1.25/0.13mm Accesories- Camera attachement.
			_			
						· ·

(Dr. Y.R.Patil)
Dean
ved H

Govt. Ayurved Hospital, Nanded.